



DOWNLIGHT PRODUCT GUIDE

	QUICKSHIP		LITE	SPEC GRADE										
														
	4RCD/6RCD	4FDR/6FDR	4LDR/6LDR	2D	2A	V2D	4D/6D	4A/6A	4P/6P	HM4/HM6	HS4/HS6	M4P/M6P	V4D/V6D	8D
ROUND	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SQUARE				✓	✓		✓		✓			✓		
ADJUSTABLE					✓			✓						
SHALLOW PLENUM									✓			✓		
MRI												✓		
MAX DELIVERED LUMENS	1,000/2,200	2,000	3,000	2,500	1,500	1,800	7,000/12,000	4,000	7,000	4,000/6,000	4,000/6,000	5,000	3,700/5,600	9,000
BEAM ANGLES	W	W	W	W, M, N, S	W, M, N	W	W, M, N, WW	W, M, N	W, M, N	W, M, N	W, M, N	W, M, N	W, M, N	W, M, N, S
OVERLAPPING FLANGE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SLIM FLANGE MUD-IN							✓	✓	✓					
ZERO FLANGE MUD-IN				✓	✓									
MOUNTING														
NEW CONSTRUCTION	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
REMODEL	✓	✓	✓	✓	✓		✓	✓	✓					✓
IC-RATED	✓	✓	✓	✓	✓		✓	✓	✓	✓		✓	✓	✓
LISTINGS														
IP65-RATED							✓		✓	✓	✓	✓	✓	
NSF										✓	✓			
ISO 5										✓	✓		✓	
MIL STD 461G											✓			
CHICAGO PLENUM (CCEA)			✓	✓	✓		✓	✓	✓	✓		✓	✓	✓
TITLE 24 JA8 COMPLIANT				✓			✓							
WET/CC	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
BAA COMPLIANT		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
BABA COMPLIANT			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
OPTIONS														
SLOPED CEILING ADAPTER							Round only							✓
AIRTIGHT CONSTRUCTION			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
INTEGRAL TEST SWITCH			✓				Round only							
TUNABLE WHITE				✓	✓		✓	✓	✓			✓	✓	✓
DIM TO WARM				✓	✓		✓	✓	✓			✓	✓	✓
FIELDSELECT	✓	✓												
ANTI-MICROBIAL				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
EMERGENCY		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IN-FIXTURE CONTROLS				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
TRIM														
OPEN REFLECTOR				Round only	Round only		Round only	✓						✓
OPEN + TOP DIFFUSER	✓	✓	✓	✓			✓							
FLUSH LENS				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
REGRESSED LENS				✓	✓	✓	✓			✓	✓		✓	
ANGLED LENS				✓	Round only		✓	✓	Round only					
DEAD-FRONT SHOWER							Round only		Round only					
TAMPER-RESISTANT						✓							✓	