



HIGH BAY PRODUCT GUIDE

	GFR FieldSELECT Round		GMR NSF-Rated Round		GS Slim		GA Narrow Aisle		GH Compact		GL Low-Profile		GP Performance
	Click for more info →												
LUMEN OUTPUT	16,000 to 35,000	15,500 to 37,600	12,000 to 48,000	3,500 to 18,000	8,000 to 72,000	15,000 to 80,000	9,300 to 74,000						
MAX EFFICACY	167 lm/W	148 lm/W	155 lm/W	186 lm/W	187 lm/W	188 lm/W	140 lm/W						
LENGTH	11" or 13" Round	17" Round	2' 4'	4' 8'	2' 4'	4'	2'						
AMBIENT TEMP	-40°C to 50°C	-40°C to 55°C	55°C Max	40°C Max	55°C Max	60°C Max	-35°C to 65°C						
DISTRIBUTION	M	W	N M	N	N M	N M	N M W						
ALUMINUM HOUSING	✓	✓	✓			✓	✓						
STEEL HOUSING				✓	✓								
LOW-PROFILE			✓	✓	✓	✓							
LISTINGS													
NSF CERTIFIED		✓											
IP RATED	IP65	IP66											
IK09 RATED	✓												
PSI WASH RATED		✓											
UL 924				✓									
QUICKSHIP			✓										
BAA COMPLIANT		✓	✓	✓	✓	✓	✓			✓		✓	
BABA COMPLIANT			✓	✓	✓	✓	✓			✓		✓	
DLC QUALIFIED	✓		✓		✓								
SHIELDING													
OPEN (NO LENS)			✓	✓	✓	✓	✓			✓		✓	
ACRYLIC		✓	✓		✓	✓	✓			✓			
POLYCARBONATE	✓	✓				✓						✓	
OPTIONS													
UPLIGHT					✓			✓		✓		✓	
EMERGENCY	✓	✓	✓	✓	✓	✓	✓			✓		✓	
OCCUPANCY SENSOR	✓		✓	✓	✓	✓	✓			✓		✓	
WIREGUARD			✓		✓			✓		✓		✓	
REFLECTOR	✓												
IN-FIXTURE CONTROLS			✓	✓	✓	✓	✓			✓		✓	