



VAPOR-TIGHT INDUSTRIAL PRODUCT GUIDE

Click for
more info →



GNR
Round High Bay



96
Narrow Enclosed & Gasketed



97
Garage Light



EGL
Enclosed & Gasketed



HZL
Hazardous Location

LUMEN OUTPUT	15,500 to 37,600	2,100 to 22,000	2,500 to 9,500	10,700 to 40,000	10,700 to 40,000
MAX EFFICACY	148 lm/W	137 lm/W	148 lm/W	154 lm/W	161 lm/W
LENGTH	17" Round	2' 4' 8'	2' 4'	4'	4'
AMBIENT TEMP	-40°C to +55°	-40°C to +40°	-40°C to +40°	-40°C to +40°	-20°C to +40°
ENCLOSURE	Aluminum	Fiberglass	Fiberglass	Fiberglass	Fiberglass
MOUNTING	Suspended	Suspended, Surface, Wall	Suspended, Surface	Suspended, Surface	Suspended, Surface

LISTINGS

CLASS 1-3, DIV 2					✓
PSI WASH RATED	✓	✓	✓	✓	✓
NEMA 4X		✓	✓	✓	✓
IP65		✓	✓	✓	✓
IP66	✓	✓	✓	✓	✓
IP67		✓	✓	✓	✓
NSF	✓	✓	✓	✓	✓
BAA	✓	✓	✓	✓	✓
BABA		✓	✓	✓	✓
DLC QUALIFIED				✓	
WET LOCATION	✓	✓	✓	✓	✓

ACRYLIC SHIELDING

RIBBED FROSTED		✓			
SMOOTH FROSTED		✓	✓	✓	✓
DROP FROSTED		✓			
DROP CLEAR		✓			
SMOOTH CLEAR	✓	✓	✓	✓	✓

POLYCARBONATE SHIELDING

RIBBED FROSTED		✓			
SMOOTH FROSTED		✓			
SMOOTH CLEAR	✓	✓		✓	✓

OPTIONS

EMERGENCY	✓	✓	✓	✓	✓
OCCUPANCY SENSOR		✓	✓	✓	
VANDAL-RESISTANT		✓	✓	✓	✓
IN-FIXTURE CONTROLS		✓	✓	✓	