



IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] GEN FROM 13257153.18
 [TESTLAB] UL Verification Services Inc.
 [ISSUEDATE] 02/08/2021
 [MANUFAC] WILLIAMS INDOOR
 [OTHER] H.E. WILLIAMS, INC. - CARTHAGE, MO.
 [LUMCAT] 4CS-L15-835-xxx-DIM-UNV-OM-CS
 [LUMINAIRE] Square cylinder housing, optics, and trim enclosure
 [LAMP] One white LED
 [_SEARCH_SOURCETYPE] LED
 [_SEARCH_APPLICATION] Indoor, Downlight
 [_SEARCH_MOUNTING] Surface, Suspended, Wall

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1099
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	64
Total Luminaire Watts	17.2972
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.74
Spacing Criterion (90-270)	0.74
Spacing Criterion (Diagonal)	0.78
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.21 ft
Luminous Width (90-270)	0.21 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	55646	50127	58353
55	29988	29165	31245
65	941	6881	1000
75	480	480	480
85	285	285	285

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>
0.0	1386.0	1386.0	1386.0	1386.0	1386.0
0.5	1386.0	1386.0	1384.0	1385.0	1386.0
1.0	1385.0	1385.0	1383.0	1383.0	1385.0
1.5	1382.0	1383.0	1380.0	1381.0	1382.0
2.0	1379.0	1379.0	1377.0	1377.0	1379.0
2.5	1375.0	1375.0	1372.0	1373.0	1374.0
3.0	1369.0	1369.0	1367.0	1368.0	1368.0
3.5	1362.0	1363.0	1360.0	1361.0	1362.0
4.0	1355.0	1355.0	1353.0	1354.0	1354.0
4.5	1347.0	1347.0	1345.0	1345.0	1346.0
5.0	1337.0	1338.0	1336.0	1336.0	1337.0
5.5	1328.0	1328.0	1326.0	1327.0	1327.0
6.0	1317.0	1318.0	1315.0	1316.0	1317.0
6.5	1307.0	1307.0	1304.0	1305.0	1306.0
7.0	1295.0	1295.0	1293.0	1294.0	1294.0
7.5	1283.0	1283.0	1281.0	1281.0	1282.0
8.0	1270.0	1270.0	1268.0	1269.0	1269.0
8.5	1257.0	1257.0	1255.0	1256.0	1255.0
9.0	1243.0	1243.0	1242.0	1242.0	1242.0
9.5	1228.0	1229.0	1228.0	1228.0	1228.0
10.0	1213.0	1214.0	1213.0	1213.0	1212.0
10.5	1198.0	1198.0	1198.0	1198.0	1197.0
11.0	1180.0	1182.0	1184.0	1182.0	1180.0
11.5	1164.0	1166.0	1168.0	1165.0	1163.0
12.0	1146.0	1148.0	1152.0	1148.0	1145.0
12.5	1128.0	1131.0	1135.0	1130.0	1127.0
13.0	1110.0	1113.0	1118.0	1113.0	1109.0
13.5	1091.0	1095.0	1101.0	1095.0	1091.0
14.0	1072.0	1076.0	1083.0	1077.0	1072.0
14.5	1052.0	1058.0	1065.0	1058.0	1053.0
15.0	1034.0	1039.0	1046.0	1039.0	1033.0
15.5	1013.0	1020.0	1027.0	1019.0	1014.0
16.0	994.3	1000.0	1007.0	999.9	993.9
16.5	974.3	981.2	988.1	980.8	974.5
17.0	954.6	961.8	968.1	961.2	955.0
17.5	934.8	942.2	948.0	941.5	934.9
18.0	914.8	922.7	927.6	921.8	914.4
18.5	895.3	903.1	908.0	902.2	893.9
19.0	875.8	883.0	887.7	882.1	874.1
19.5	855.7	863.2	867.2	862.7	853.8
20.0	835.4	843.3	847.5	842.5	833.7
20.5	815.5	823.4	827.1	822.7	813.3
21.0	795.0	803.9	807.0	802.6	793.7
21.5	775.2	784.0	787.2	783.6	774.7
22.0	757.1	765.7	768.9	764.5	754.8
22.5	738.9	746.6	749.0	744.6	734.7
23.0	720.2	728.6	730.6	725.1	716.4
23.5	700.6	709.0	711.2	707.0	697.1
24.0	681.0	689.5	691.6	687.3	677.1
24.5	661.3	670.2	672.0	667.8	657.1
25.0	641.3	650.9	652.9	648.3	637.1
25.5	621.3	631.5	634.0	628.9	617.1
26.0	601.0	612.5	615.4	609.8	597.1
26.5	580.4	593.3	596.8	590.5	576.8

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

CANDELA TABULATION - (Cont.)

27.0	559.7	574.1	578.5	571.5	556.9
27.5	539.2	555.0	560.7	552.3	537.3
28.0	518.9	536.0	543.0	533.3	517.9
28.5	499.1	517.2	525.6	514.5	498.8
29.0	479.7	498.5	508.7	496.2	480.3
29.5	461.2	480.1	492.1	478.1	462.6
30.0	443.3	461.8	475.7	460.4	445.3
30.5	425.9	444.0	459.2	443.0	428.5
31.0	409.3	426.6	443.1	426.0	412.3
31.5	393.4	409.9	427.4	409.6	396.9
32.0	378.4	393.8	412.1	393.9	382.3
32.5	364.1	378.3	397.1	378.9	368.4
33.0	350.4	363.4	382.3	364.4	355.1
33.5	337.4	349.1	367.8	350.5	342.3
34.0	325.0	335.5	353.7	337.2	330.3
34.5	313.3	322.5	339.9	324.6	318.8
35.0	302.4	310.1	326.6	312.5	308.1
35.5	291.9	298.4	313.6	301.2	297.8
36.0	281.9	287.1	300.9	290.3	288.1
36.5	272.3	276.3	288.6	279.8	278.9
37.0	263.2	266.1	276.6	269.8	270.1
37.5	254.5	256.2	264.8	260.3	261.5
38.0	246.1	246.8	253.5	251.1	253.3
38.5	238.1	237.9	242.7	242.4	245.7
39.0	230.4	229.3	232.4	234.1	238.2
39.5	222.9	221.1	222.4	226.1	231.0
40.0	215.9	213.2	212.9	218.5	224.0
40.5	209.0	205.6	203.9	211.1	217.3
41.0	202.5	198.4	195.3	204.0	210.9
41.5	196.2	191.6	187.3	197.3	204.6
42.0	190.2	185.1	179.9	190.9	198.6
42.5	184.4	178.9	172.7	184.7	192.8
43.0	178.8	172.9	166.0	178.7	187.1
43.5	173.4	167.1	159.6	172.9	181.6
44.0	168.2	161.6	153.6	167.3	176.3
44.5	163.2	156.3	148.0	162.0	171.1
45.0	158.3	151.2	142.6	156.8	166.0
45.5	153.4	146.2	137.6	151.8	161.0
46.0	148.6	141.4	132.8	147.0	156.0
46.5	143.9	136.7	128.1	142.2	151.1
47.0	139.3	132.0	123.7	137.4	146.2
47.5	134.8	127.5	119.4	132.9	141.3
48.0	130.3	123.2	115.3	128.4	136.5
48.5	125.8	118.8	111.5	124.0	131.7
49.0	121.3	114.6	107.6	119.8	126.9
49.5	117.0	110.5	103.8	115.6	122.2
50.0	112.5	106.4	100.1	111.3	117.4
50.5	108.2	102.5	96.6	107.3	112.8
51.0	103.9	98.6	93.1	103.3	108.2
51.5	99.5	94.9	89.8	99.4	103.5
52.0	95.1	91.2	86.5	95.6	98.8
52.5	90.6	87.4	83.2	91.8	94.3
53.0	86.2	83.8	79.9	88.1	89.7
53.5	81.9	80.3	76.7	84.4	85.3
54.0	77.6	77.0	73.5	80.8	80.8
54.5	73.4	73.5	70.3	77.2	76.4

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

CANDELA TABULATION - (Cont.)

55.0	69.2	70.1	67.3	73.6	72.1
55.5	65.0	66.7	64.2	70.1	67.8
56.0	61.1	63.3	61.0	66.5	63.7
56.5	57.1	60.0	58.0	63.0	59.5
57.0	53.2	56.8	55.0	59.5	55.4
57.5	49.4	53.5	52.0	56.0	51.3
58.0	45.6	50.2	49.0	52.6	47.3
58.5	41.8	47.0	46.0	49.1	43.1
59.0	38.0	43.7	43.1	45.6	38.8
59.5	34.2	40.5	40.2	42.1	34.6
60.0	30.1	37.2	37.4	38.6	30.3
60.5	25.9	33.9	34.6	35.0	26.3
61.0	21.7	30.6	31.8	31.3	22.4
61.5	17.7	27.1	29.1	27.5	18.6
62.0	14.2	23.5	26.4	23.7	14.3
62.5	11.2	19.8	23.8	20.1	10.4
63.0	8.4	16.3	21.2	16.6	8.2
63.5	4.1	13.0	18.7	13.3	6.5
64.0	2.0	9.9	16.3	9.9	5.0
64.5	1.8	7.1	13.9	7.1	2.7
65.0	1.6	5.0	11.7	5.4	1.7
65.5	1.5	3.3	9.7	4.0	1.6
66.0	1.4	2.0	7.8	2.7	1.5
66.5	1.3	1.3	6.2	1.6	1.4
67.0	1.3	1.2	4.8	1.3	1.3
67.5	1.2	1.1	3.7	1.2	1.3
68.0	1.1	1.1	2.8	1.1	1.2
68.5	1.1	1.0	2.1	1.0	1.1
69.0	1.0	0.9	1.7	1.0	1.0
69.5	0.9	0.9	1.3	0.9	1.0
70.0	0.9	0.8	1.1	0.9	0.9
70.5	0.8	0.8	0.9	0.8	0.9
71.0	0.8	0.7	0.8	0.8	0.8
71.5	0.7	0.7	0.7	0.7	0.8
72.0	0.7	0.7	0.7	0.7	0.7
72.5	0.6	0.6	0.6	0.6	0.7
73.0	0.6	0.6	0.6	0.6	0.6
73.5	0.6	0.5	0.6	0.6	0.6
74.0	0.5	0.5	0.5	0.5	0.6
74.5	0.5	0.5	0.5	0.5	0.5
75.0	0.5	0.5	0.5	0.5	0.5
75.5	0.5	0.4	0.4	0.4	0.5
76.0	0.4	0.4	0.4	0.4	0.4
76.5	0.4	0.4	0.4	0.4	0.4
77.0	0.4	0.4	0.4	0.4	0.4
77.5	0.3	0.3	0.3	0.3	0.4
78.0	0.3	0.3	0.3	0.3	0.3
78.5	0.3	0.3	0.3	0.3	0.3
79.0	0.3	0.3	0.3	0.3	0.3
79.5	0.3	0.2	0.3	0.3	0.3
80.0	0.2	0.2	0.2	0.2	0.3
80.5	0.2	0.2	0.2	0.2	0.2
81.0	0.2	0.2	0.2	0.2	0.2
81.5	0.2	0.2	0.2	0.2	0.2
82.0	0.2	0.2	0.2	0.2	0.2
82.5	0.2	0.2	0.2	0.2	0.2

IES INDOOR REPORT
 PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

CANDELA TABULATION - (Cont.)

83.0	0.2	0.1	0.2	0.2	0.2
83.5	0.1	0.1	0.1	0.1	0.1
84.0	0.1	0.1	0.1	0.1	0.1
84.5	0.1	0.1	0.1	0.1	0.1
85.0	0.1	0.1	0.1	0.1	0.1
85.5	0.1	0.1	0.1	0.1	0.1
86.0	0.1	0.1	0.1	0.1	0.1
86.5	0.1	0.1	0.1	0.1	0.1
87.0	0.1	0.1	0.1	0.1	0.1
87.5	0.1	0.1	0.1	0.1	0.1
88.0	0.1	0.1	0.0	0.1	0.1
88.5	0.1	0.0	0.0	0.0	0.0
89.0	0.0	0.0	0.0	0.0	0.1
89.5	0.0	0.0	0.0	0.0	0.0
90.0	0.0	0.0	0.0	0.0	0.0
90.5	0.0	0.0	0.0	0.0	0.0
91.0	0.0	0.0	0.0	0.0	0.0
91.5	0.0	0.0	0.0	0.0	0.0
92.0	0.0	0.0	0.0	0.0	0.0
92.5	0.0	0.0	0.0	0.0	0.0
93.0	0.0	0.0	0.0	0.0	0.0
93.5	0.0	0.0	0.0	0.0	0.0
94.0	0.0	0.0	0.0	0.0	0.0
94.5	0.0	0.0	0.0	0.0	0.0
95.0	0.0	0.0	0.0	0.0	0.0
95.5	0.0	0.0	0.0	0.0	0.0
96.0	0.0	0.0	0.0	0.0	0.0
96.5	0.0	0.0	0.0	0.0	0.0
97.0	0.0	0.0	0.0	0.0	0.0
97.5	0.0	0.0	0.0	0.0	0.0
98.0	0.0	0.0	0.0	0.0	0.0
98.5	0.0	0.0	0.0	0.0	0.0
99.0	0.0	0.0	0.0	0.0	0.0
99.5	0.0	0.0	0.0	0.0	0.0
100.0	0.0	0.0	0.0	0.0	0.0
100.5	0.0	0.0	0.0	0.0	0.0
101.0	0.0	0.0	0.0	0.0	0.0
101.5	0.0	0.0	0.0	0.0	0.0
102.0	0.0	0.0	0.0	0.0	0.0
102.5	0.0	0.0	0.0	0.0	0.0
103.0	0.0	0.0	0.0	0.0	0.0
103.5	0.0	0.0	0.0	0.0	0.0
104.0	0.0	0.0	0.0	0.0	0.0
104.5	0.0	0.0	0.0	0.0	0.0
105.0	0.0	0.0	0.0	0.0	0.0
105.5	0.0	0.0	0.0	0.0	0.0
106.0	0.0	0.0	0.0	0.0	0.0
106.5	0.0	0.0	0.0	0.0	0.0
107.0	0.0	0.0	0.0	0.0	0.0
107.5	0.0	0.0	0.0	0.0	0.0
108.0	0.0	0.0	0.0	0.0	0.0
108.5	0.0	0.0	0.0	0.0	0.0
109.0	0.0	0.0	0.0	0.0	0.0
109.5	0.0	0.0	0.0	0.0	0.0
110.0	0.0	0.0	0.0	0.0	0.0
110.5	0.0	0.0	0.0	0.0	0.0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

CANDELA TABULATION - (Cont.)

111.0	0.0	0.0	0.0	0.0	0.0
111.5	0.0	0.0	0.0	0.0	0.0
112.0	0.0	0.0	0.0	0.0	0.0
112.5	0.0	0.0	0.0	0.0	0.0
113.0	0.0	0.0	0.0	0.0	0.0
113.5	0.0	0.0	0.0	0.0	0.0
114.0	0.0	0.0	0.0	0.0	0.0
114.5	0.0	0.0	0.0	0.0	0.0
115.0	0.0	0.0	0.0	0.0	0.0
115.5	0.0	0.0	0.0	0.0	0.0
116.0	0.0	0.0	0.0	0.0	0.0
116.5	0.0	0.0	0.0	0.0	0.0
117.0	0.0	0.0	0.0	0.0	0.0
117.5	0.0	0.0	0.0	0.0	0.0
118.0	0.0	0.0	0.0	0.0	0.0
118.5	0.0	0.0	0.0	0.0	0.0
119.0	0.0	0.0	0.0	0.0	0.0
119.5	0.0	0.0	0.0	0.0	0.0
120.0	0.0	0.0	0.0	0.0	0.0
120.5	0.0	0.0	0.0	0.0	0.0
121.0	0.0	0.0	0.0	0.0	0.0
121.5	0.0	0.0	0.0	0.0	0.0
122.0	0.0	0.0	0.0	0.0	0.0
122.5	0.0	0.0	0.0	0.0	0.0
123.0	0.0	0.0	0.0	0.0	0.0
123.5	0.0	0.0	0.0	0.0	0.0
124.0	0.0	0.0	0.0	0.0	0.0
124.5	0.0	0.0	0.0	0.0	0.0
125.0	0.0	0.0	0.0	0.0	0.0
125.5	0.0	0.0	0.0	0.0	0.0
126.0	0.0	0.0	0.0	0.0	0.0
126.5	0.0	0.0	0.0	0.0	0.0
127.0	0.0	0.0	0.0	0.0	0.0
127.5	0.0	0.0	0.0	0.0	0.0
128.0	0.0	0.0	0.0	0.0	0.0
128.5	0.0	0.0	0.0	0.0	0.0
129.0	0.0	0.0	0.0	0.0	0.0
129.5	0.0	0.0	0.0	0.0	0.0
130.0	0.0	0.0	0.0	0.0	0.0
130.5	0.0	0.0	0.0	0.0	0.0
131.0	0.0	0.0	0.0	0.0	0.0
131.5	0.0	0.0	0.0	0.0	0.0
132.0	0.0	0.0	0.0	0.0	0.0
132.5	0.0	0.0	0.0	0.0	0.0
133.0	0.0	0.0	0.0	0.0	0.0
133.5	0.0	0.0	0.0	0.0	0.0
134.0	0.0	0.0	0.0	0.0	0.0
134.5	0.0	0.0	0.0	0.0	0.0
135.0	0.0	0.0	0.0	0.0	0.0
135.5	0.0	0.0	0.0	0.0	0.0
136.0	0.0	0.0	0.0	0.0	0.0
136.5	0.0	0.0	0.0	0.0	0.0
137.0	0.0	0.0	0.0	0.0	0.0
137.5	0.0	0.0	0.0	0.0	0.0
138.0	0.0	0.0	0.0	0.0	0.0
138.5	0.0	0.0	0.0	0.0	0.0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

CANDELA TABULATION - (Cont.)

139.0	0.0	0.0	0.0	0.0	0.0
139.5	0.0	0.0	0.0	0.0	0.0
140.0	0.0	0.0	0.0	0.0	0.0
140.5	0.0	0.0	0.0	0.0	0.0
141.0	0.0	0.0	0.0	0.0	0.0
141.5	0.0	0.0	0.0	0.0	0.0
142.0	0.0	0.0	0.0	0.0	0.0
142.5	0.0	0.0	0.0	0.0	0.0
143.0	0.0	0.0	0.0	0.0	0.0
143.5	0.0	0.0	0.0	0.0	0.0
144.0	0.0	0.0	0.0	0.0	0.0
144.5	0.0	0.0	0.0	0.0	0.0
145.0	0.0	0.0	0.0	0.0	0.0
145.5	0.0	0.0	0.0	0.0	0.0
146.0	0.0	0.0	0.0	0.0	0.0
146.5	0.0	0.0	0.0	0.0	0.0
147.0	0.0	0.0	0.0	0.0	0.0
147.5	0.0	0.0	0.0	0.0	0.0
148.0	0.0	0.0	0.0	0.0	0.0
148.5	0.0	0.0	0.0	0.0	0.0
149.0	0.0	0.0	0.0	0.0	0.0
149.5	0.0	0.0	0.0	0.0	0.0
150.0	0.0	0.0	0.0	0.0	0.0
150.5	0.0	0.0	0.0	0.0	0.0
151.0	0.0	0.0	0.0	0.0	0.0
151.5	0.0	0.0	0.0	0.0	0.0
152.0	0.0	0.0	0.0	0.0	0.0
152.5	0.0	0.0	0.0	0.0	0.0
153.0	0.0	0.0	0.0	0.0	0.0
153.5	0.0	0.0	0.0	0.0	0.0
154.0	0.0	0.0	0.0	0.0	0.0
154.5	0.0	0.0	0.0	0.0	0.0
155.0	0.0	0.0	0.0	0.0	0.0
155.5	0.0	0.0	0.0	0.0	0.0
156.0	0.0	0.0	0.0	0.0	0.0
156.5	0.0	0.0	0.0	0.0	0.0
157.0	0.0	0.0	0.0	0.0	0.0
157.5	0.0	0.0	0.0	0.0	0.0
158.0	0.0	0.0	0.0	0.0	0.0
158.5	0.0	0.0	0.0	0.0	0.0
159.0	0.0	0.0	0.0	0.0	0.0
159.5	0.0	0.0	0.0	0.0	0.0
160.0	0.0	0.0	0.0	0.0	0.0
160.5	0.0	0.0	0.0	0.0	0.0
161.0	0.0	0.0	0.0	0.0	0.0
161.5	0.0	0.0	0.0	0.0	0.0
162.0	0.0	0.0	0.0	0.0	0.0
162.5	0.0	0.0	0.0	0.0	0.0
163.0	0.0	0.0	0.0	0.0	0.0
163.5	0.0	0.0	0.0	0.0	0.0
164.0	0.0	0.0	0.0	0.0	0.0
164.5	0.0	0.0	0.0	0.0	0.0
165.0	0.0	0.0	0.0	0.0	0.0
165.5	0.0	0.0	0.0	0.0	0.0
166.0	0.0	0.0	0.0	0.0	0.0
166.5	0.0	0.0	0.0	0.0	0.0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

CANDELA TABULATION - (Cont.)

167.0	0.0	0.0	0.0	0.0	0.0
167.5	0.0	0.0	0.0	0.0	0.0
168.0	0.0	0.0	0.0	0.0	0.0
168.5	0.0	0.0	0.0	0.0	0.0
169.0	0.0	0.0	0.0	0.0	0.0
169.5	0.0	0.0	0.0	0.0	0.0
170.0	0.0	0.0	0.0	0.0	0.0
170.5	0.0	0.0	0.0	0.0	0.0
171.0	0.0	0.0	0.0	0.0	0.0
171.5	0.0	0.0	0.0	0.0	0.0
172.0	0.0	0.0	0.0	0.0	0.0
172.5	0.0	0.0	0.0	0.0	0.0
173.0	0.0	0.0	0.0	0.0	0.0
173.5	0.0	0.0	0.0	0.0	0.0
174.0	0.0	0.0	0.0	0.0	0.0
174.5	0.0	0.0	0.0	0.0	0.0
175.0	0.0	0.0	0.0	0.0	0.0
175.5	0.0	0.0	0.0	0.0	0.0
176.0	0.0	0.0	0.0	0.0	0.0
176.5	0.0	0.0	0.0	0.0	0.0
177.0	0.0	0.0	0.0	0.0	0.0
177.5	0.0	0.0	0.0	0.0	0.0
178.0	0.0	0.0	0.0	0.0	0.0
178.5	0.0	0.0	0.0	0.0	0.0
179.0	0.0	0.0	0.0	0.0	0.0
179.5	0.0	0.0	0.0	0.0	0.0
180.0	0.0	0.0	0.0	0.0	0.0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	411.35	N.A.	37.40
0-30	705.99	N.A.	64.20
0-40	905.11	N.A.	82.40
0-60	1087.85	N.A.	99.00
0-80	1098.92	N.A.	100.00
0-90	1099.04	N.A.	100.00
10-90	975.43	N.A.	88.80
20-40	493.76	N.A.	44.90
20-50	613.49	N.A.	55.80
40-70	193.28	N.A.	17.60
60-80	11.06	N.A.	1.00
70-80	0.53	N.A.	0.00
80-90	0.12	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1099.04	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	123.61
10-20	287.74
20-30	294.64
30-40	199.12
40-50	119.73
50-60	63.02
60-70	10.54
70-80	0.53
80-90	0.12
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85
3	101	94	89	85	99	93	88	84	90	86	83	88	84	81	85	83	80	78
4	96	88	82	77	94	86	81	77	84	79	76	82	78	75	80	77	74	72
5	90	81	75	71	89	81	75	70	79	74	70	77	73	69	75	72	68	67
6	86	76	70	65	84	75	69	65	74	68	65	72	68	64	71	67	64	62
7	81	71	65	61	80	71	65	60	69	64	60	68	63	60	67	63	59	58
8	77	67	61	56	76	66	60	56	65	60	56	64	59	56	63	59	56	54
9	73	63	57	53	72	63	57	53	62	56	53	61	56	52	60	55	52	51
10	70	60	54	50	69	59	53	50	58	53	49	58	53	49	57	52	49	48

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4CS-L15-835-XXX-DIM-UNV-OM-CS.IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size UGR Viewed Crosswise


X=2H	Y=2H	19.6	20.7	19.9	21.0	21.3	19.9	21.0	20.2	21.3	21.6
	3H	19.4	20.4	19.8	20.7	21.1	19.7	20.7	20.1	21.0	21.4
	4H	19.3	20.2	19.7	20.6	20.9	19.6	20.5	20.0	20.9	21.3
	6H	19.2	20.0	19.6	20.4	20.8	19.5	20.3	19.9	20.7	21.1
	8H	19.2	19.9	19.6	20.3	20.7	19.5	20.2	19.9	20.6	21.0
	12H	19.1	19.8	19.5	20.2	20.7	19.4	20.2	19.8	20.5	21.0

UGR Viewed Endwise

4H	2H	19.4	20.3	19.8	20.7	21.0	19.7	20.6	20.1	21.0	21.3
	3H	19.2	20.0	19.6	20.4	20.8	19.5	20.3	19.9	20.7	21.1
	4H	19.1	19.8	19.5	20.2	20.6	19.4	20.1	19.8	20.5	20.9
	6H	19.0	19.6	19.5	20.0	20.5	19.3	19.9	19.8	20.3	20.8
	8H	19.0	19.5	19.4	19.9	20.4	19.3	19.8	19.7	20.2	20.7
	12H	18.9	19.3	19.4	19.8	20.3	19.2	19.6	19.7	20.1	20.6
8H	4H	19.0	19.5	19.4	19.9	20.4	19.3	19.8	19.7	20.2	20.7
	6H	18.8	19.2	19.3	19.7	20.2	19.1	19.5	19.6	20.0	20.5
	8H	18.8	19.1	19.3	19.6	20.1	19.1	19.4	19.6	20.0	20.4
	12H	18.7	19.0	19.2	19.5	20.1	19.0	19.3	19.5	19.8	20.4
12H	4H	18.9	19.3	19.4	19.8	20.3	19.2	19.6	19.7	20.1	20.6
	6H	18.8	19.1	19.3	19.6	20.2	19.1	19.4	19.6	19.9	20.5
	8H	18.7	19.0	19.2	19.5	20.1	19.0	19.3	19.5	19.8	20.4

Maximum UGR = 21.6

POLAR GRAPH



Maximum Candela = 1386 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)