

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 4DR-TL-L40-835-DIM-UNV-FW-OF-SG_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST]GEN FROM BALLABS TEST NO. 20685.0

[TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC

[ISSUE DATE] 01-10-2025

[MANUFAC] WILLIAMS INDOOR

[OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO

[LUMINAIRE] 1 BRIDGELUX V13 LED 4"RND RECESSED CAST HOUSING DOWNLIGHT

[MORE] OPEN SATIN GLOW SPUN ALUMINUM REFLECTOR (WIDE)

[LUMCAT] 4DR-TL-L40-835-DIM-UNV-FW-OF-SG

[LAMPCAT] V13 BXRE-35E2000

[_SEARCH_SOURCETYPE] LED

[_SEARCH_APPLICATION] Indoor, Classroom, Commercial, Corridor, Hotel, Industrial, Office, Downlight

[_SEARCH_MOUNTING] Recessed

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2745
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	72
Total Luminaire Watts	38
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.22
Spacing Criterion (90-270)	1.22
Spacing Criterion (Diagonal)	0.94
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.37 ft (Diameter)
Luminous Width (90-270)	0.37 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	8325	8325	8325
55	2566	2566	2566
65	317	317	317
75	0	0	0
85	0	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4DR-TL-L40-835-DIM-UNV-FW-OF-SG_.IES

CANDELA TABULATION

	<u>0</u>
0	2356.271
5	2426.568
10	2499.470
15	2551.542
20	2664.799
25	2904.332
30	2275.559
35	399.655
40	104.145
45	57.280
50	29.942
55	14.320
60	6.509
65	1.302
70	1.302
75	0.000
80	0.000
85	0.000
90	0.000

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4DR-TL-L40-835-DIM-UNV-FW-OF-SG_.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	962.92	N.A.	35.10
0-30	2202.54	N.A.	80.20
0-40	2680.54	N.A.	97.60
0-60	2742.49	N.A.	99.90
0-80	2745.39	N.A.	100.00
0-90	2745.39	N.A.	100.00
10-90	2511.99	N.A.	91.50
20-40	1717.62	N.A.	62.60
20-50	1765.13	N.A.	64.30
40-70	64.51	N.A.	2.30
60-80	2.90	N.A.	0.10
70-80	0.34	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	2745.39	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	233.40
10-20	729.52
20-30	1239.62
30-40	478.00
40-50	47.51
50-60	14.44
60-70	2.56
70-80	0.34
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4DR-TL-L40-835-DIM-UNV-FW-OF-SG_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	102	101	100	99	98	97	96	94
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88
3	103	97	92	88	101	95	91	88	93	89	86	90	87	85	88	86	83	82
4	98	91	85	81	96	90	85	81	87	83	80	85	82	79	84	81	78	77
5	93	85	79	75	92	84	79	75	82	78	74	81	77	74	79	76	73	72
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59
9	76	67	61	57	75	66	61	57	66	60	57	65	60	57	64	60	57	55
10	73	63	58	54	72	63	57	54	62	57	54	61	57	53	61	56	53	52


IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4DR-TL-L40-835-DIM-UNV-FW-OF-SG_.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	3H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	4H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	6H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	8H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	12H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
4H	2H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	3H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	4H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	6H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	8H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	12H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
8H	4H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	6H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	8H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	12H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
12H	4H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	6H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	8H	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5

Maximum UGR = 3.5

POLAR GRAPH



Maximum Candela = 2904.332 Located At Horizontal Angle = 0, Vertical Angle = 25
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (25) (Through Max. Cd.)