

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6CR-TL-L50-850-XXX-DIM-UNV-OW-CS-XX_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] GEN FROM BALLABS TEST NO. 20685.0

[TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC

[ISSUE DATE] 08/05/2025

[MANUFAC] WILLIAMS INDOOR

[OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO

[LUMINAIRE] 6" RND CYLINDER LED DOWNLIGHT

[MORE] OPEN SEMI-SPEC SPUN ALUMINUM REFLECTOR (WIDE)

[LUMCAT] 6CR-TL-L50-850-xxx-DIM-UNV-OW-CS-xx

[_SEARCH_SOURCETYPE] LED

[_SEARCH_APPLICATION] Indoor, Classroom, Commercial, Corridor, Hotel, Industrial, Office, Downlight

[_SEARCH_MOUNTING] Recessed

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5226
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	116
Total Luminaire Watts	45.2
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.22
Spacing Criterion (90-270)	1.22
Spacing Criterion (Diagonal)	0.94
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.37 ft (Diameter)
Luminous Width (90-270)	0.37 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	15849	15849	15849
55	4885	4885	4885
65	603	603	603
75	0	0	0
85	0	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 6CR-TL-L50-850-XXX-DIM-UNV-OW-CS-XX_.IES

CANDELA TABULATION

	<u>0</u>
0	4485.504
5	4619.326
10	4758.104
15	4857.231
20	5072.832
25	5528.817
30	4331.857
35	760.801
40	198.254
45	109.040
50	56.998
55	27.260
60	12.391
65	2.478
70	2.478
75	0.000
80	0.000
85	0.000
90	0.000

IES INDOOR REPORT**PHOTOMETRIC FILENAME : 6CR-TL-L50-850-XXX-DIM-UNV-OW-CS-XX_.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	1833.06	N.A.	35.10
0-30	4192.85	N.A.	80.20
0-40	5102.79	N.A.	97.60
0-60	5220.73	N.A.	99.90
0-80	5226.24	N.A.	100.00
0-90	5226.24	N.A.	100.00
10-90	4781.94	N.A.	91.50
20-40	3269.73	N.A.	62.60
20-50	3360.18	N.A.	64.30
40-70	122.80	N.A.	2.30
60-80	5.52	N.A.	0.10
70-80	0.65	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	5226.24	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	444.31
10-20	1388.75
20-30	2359.79
30-40	909.94
40-50	90.45
50-60	27.49
60-70	4.87
70-80	0.65
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6CR-TL-L50-850-XXX-DIM-UNV-OW-CS-XX_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	102	101	100	98	98	97	96	94
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88
3	103	97	92	88	101	95	91	88	93	89	86	90	87	85	88	86	83	82
4	98	91	85	81	96	90	85	81	87	83	80	85	82	79	84	81	78	77
5	93	85	79	75	92	84	79	75	82	78	74	81	77	74	79	76	73	72
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59
9	76	67	61	57	75	66	61	57	66	60	57	65	60	57	64	60	57	55
10	73	63	58	54	72	63	57	54	62	57	54	61	57	53	61	56	53	52

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6CR-TL-L50-850-XXX-DIM-UNV-OW-CS-XX_.IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size UGR Viewed Crosswise


X=2H	Y=2H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	3H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	4H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	6H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	8H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	12H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7

UGR Viewed Endwise

4H	2H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	3H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	4H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	6H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	8H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	12H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
8H	4H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	6H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	8H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	12H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
12H	4H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	6H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
	8H	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7

Maximum UGR = 5.7

POLAR GRAPH



Maximum Candela = 5528.817 Located At Horizontal Angle = 0, Vertical Angle = 25
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (25) (Through Max. Cd.)