



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6DR-TL-L15-840-(L11)-EM10W-DIM1-UNV-OW-OF-CS\_EM MODE ONLY.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002  
 [TEST]GEN FROM BALLABS TEST NO. 20687.0  
 [TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC  
 [ISSUE DATE] 02-28-2024  
 [MANUFAC] WILLIAMS INDOOR  
 [OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO  
 [LUMINAIRE] 6"RND RECESSED LED CAST HOUSING DOWNLIGHT  
 [MORE] OPEN SEMI-SPEC SPUN ALUMINUM REFLECTOR (WIDE)  
 [LUMCAT] 6DR-TL-L15-840-(L11)-EM10W-DIM1-UNV-OW-OF-CS  
 [LAMPCAT] V13 BXRE-35E2000  
 [ \_SEARCH\_SOURCETYPE] LED  
 [ \_SEARCH\_APPLICATION] Indoor, Architectural, Classroom, Commercial, Healthcare, Office, Downlight  
 [ \_SEARCH\_MOUNTING] Recessed

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1060
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	106
Total Luminaire Watts	10
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.26
Spacing Criterion (Diagonal)	0.98
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.48 ft (Diameter)
Luminous Width (90-270)	0.48 ft (Diameter)
Luminous Height	0.00 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1963	1963	1963
55	684	684	684
65	143	143	143
75	0	0	0
85	0	0	0

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6DR-TL-L15-840-(L11)-EM10W-DIM1-UNV-OW-OF-CS\_EM MODE ONLY.IES

## CANDELA TABULATION

	<u>0</u>
0	845.573
5	798.540
10	878.950
15	877.433
20	916.374
25	1002.347
30	984.647
35	305.458
40	41.975
45	23.263
50	13.655
55	6.574
60	3.540
65	1.011
70	0.000
75	0.000
80	0.000
85	0.000
90	0.000

**IES INDOOR REPORT****PHOTOMETRIC FILENAME : 6DR-TL-L15-840-(L11)-EM10W-DIM1-UNV-OW-OF-CS\_EM MODE ONLY.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	331.69	N.A.	31.30
0-30	784.38	N.A.	74.00
0-40	1032.32	N.A.	97.40
0-60	1058.6	N.A.	99.90
0-80	1059.96	N.A.	100.00
0-90	1059.96	N.A.	100.00
10-90	980.30	N.A.	92.50
20-40	700.64	N.A.	66.10
20-50	720.18	N.A.	67.90
40-70	27.64	N.A.	2.60
60-80	1.36	N.A.	0.10
70-80	0.00	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1059.96	N.A.	100.00

Total Luminaire Efficiency = N.A.%

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	79.66
10-20	252.02
20-30	452.69
30-40	247.94
40-50	19.54
50-60	6.74
60-70	1.36
70-80	0.00
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6DR-TL-L15-840-(L11)-EM10W-DIM1-UNV-OW-OF-CS\_EM MODE ONLY.IES

## COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	90	89	87
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81
4	97	90	84	80	95	89	83	79	86	82	79	84	81	78	83	79	77	75
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71	70
6	87	78	72	68	86	78	72	68	76	71	67	75	70	67	73	70	67	65
7	83	74	68	63	82	73	67	63	72	67	63	70	66	62	69	65	62	61
8	79	69	63	59	78	69	63	59	67	62	59	66	62	58	65	61	58	57
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	57	54	53
10	71	61	55	51	70	61	55	51	60	55	51	59	54	51	58	54	51	50

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6DR-TL-L15-840-(L11)-EM10W-DIM1-UNV-OW-OF-CS\_EM MODE ONLY.IES

## UGR TABLE - CORRECTED

### Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

### Room Size UGR Viewed Crosswise

X=2H	Y=2H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	3H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	4H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	6H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	8H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	12H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2

### UGR Viewed Endwise


4H	2H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	3H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	4H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	6H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	8H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	12H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
8H	4H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	6H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	8H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	12H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
12H	4H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	6H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	8H	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2

Maximum UGR = 0.2

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6DR-TL-L15-840-(L11)-EM10W-DIM1-UNV-OW-OF-CS\_EM MODE ONLY.IES

## POLAR GRAPH



Maximum Candela = 1002.347 Located At Horizontal Angle = 0, Vertical Angle = 25

# 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

# 2 - Horizontal Cone Through Vertical Angle (25) (Through Max. Cd.)