



IES INDOOR REPORT

PHOTOMETRIC FILENAME : 8CR-TL-L15-840-EM10W-XXX-DIM-UNV-OW-CS-XX_ EM MODE ONLY.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] GEN FROM BALLABS TEST NO. 20687.0

[TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC

[ISSUEDATE] 2-3-2021

[MANUFAC] WILLIAMS INDOOR

[OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO

[LUMINAIRE] 1 BRIDGELUX V13 LED 8" ROUND SURFACE CYLINDER

[MORE] OPEN SEMI-SPEC SPUN ALUMINUM REFLECTOR (WIDE)

[MORE] ADVANCE #XI025C070V054DSM5 @ 470mA

[LUMCAT] 8CR-L15-840-EM10W-xxx-DIM-UNV-OW-CS-xx EM MODE ONLY

[LAMPCAT] V13 BXRE-35E2000

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1086
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	109
Total Luminaire Watts	10
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.26
Spacing Criterion (Diagonal)	0.98
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.48 ft (Diameter)
Luminous Width (90-270)	0.48 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	2011	2011	2011
55	701	701	701
65	146	146	146
75	0	0	0
85	0	0	0

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 8CR-TL-L15-840-EM10W-XXX-DIM-UNV-OW-CS-XX_ EM MODE ONLY.IES

CANDELA TABULATION

	<u>0</u>
0	866.313
5	818.127
10	900.510
15	898.955
20	938.851
25	1026.933
30	1008.799
35	312.950
40	43.005
45	23.834
50	13.990
55	6.736
60	3.627
65	1.036
70	0.000
75	0.000
80	0.000
85	0.000
90	0.000

IES INDOOR REPORT**PHOTOMETRIC FILENAME : 8CR-TL-L15-840-EM10W-XXX-DIM-UNV-OW-CS-XX_ EM MODE ONLY.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	339.82	N.A.	31.30
0-30	803.62	N.A.	74.00
0-40	1057.65	N.A.	97.40
0-60	1084.57	N.A.	99.90
0-80	1085.96	N.A.	100.00
0-90	1085.96	N.A.	100.00
10-90	1004.34	N.A.	92.50
20-40	717.82	N.A.	66.10
20-50	737.84	N.A.	67.90
40-70	28.32	N.A.	2.60
60-80	1.40	N.A.	0.10
70-80	0.00	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1085.96	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	81.62
10-20	258.20
20-30	463.80
30-40	254.03
40-50	20.02
50-60	6.90
60-70	1.40
70-80	0.00
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 8CR-TL-L15-840-EM10W-XXX-DIM-UNV-OW-CS-XX_ EM MODE ONLY.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	90	89	87
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81
4	97	90	84	80	95	89	83	79	86	82	79	84	81	78	83	79	77	75
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71	70
6	87	78	72	68	86	78	72	68	76	71	67	75	70	67	73	70	67	65
7	83	74	68	63	82	73	67	63	72	67	63	70	66	62	69	65	62	61
8	79	69	63	59	78	69	63	59	67	62	59	66	62	58	65	61	58	57
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	57	54	53
10	71	61	55	51	70	61	55	51	60	55	51	59	54	51	58	54	51	50

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 8CR-TL-L15-840-EM10W-XXX-DIM-UNV-OW-CS-XX_ EM MODE ONLY.IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size UGR Viewed Crosswise

X=2H	Y=2H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	3H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	4H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	6H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	8H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	12H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3

UGR Viewed Endwise


4H	2H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	3H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	4H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	6H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	8H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	12H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
8H	4H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	6H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	8H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	12H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
12H	4H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	6H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
	8H	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3

Maximum UGR = 0.3

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 8CR-TL-L15-840-EM10W-XXX-DIM-UNV-OW-CS-XX_ EM MODE ONLY.IES

POLAR GRAPH



Maximum Candela = 1026.933 Located At Horizontal Angle = 0, Vertical Angle = 25

1 - Vertical Plane Through Horizontal Angles (90 - 270)

2 - Horizontal Cone Through Vertical Angle (25) (Through Max. Cd.)