
EMER/DECO LED Decorative Emergency Light







| CATALOG #: | | |
|------------|--|------|
| | | |
| | | |
| | | |
| | | |
| Туре: | | |
| ,, | | |
| PROJECT: | | |
| PROJECT | | |

FEATURES

- Decorative, low-profile, architectural
- Factory-installed photocell included
- Ultra-bright, energy-efficient, long-life LEDs in 5000K CCT and minimum 70 CRI
- Delivers 1286 lumens in AC mode and 350 lumens in DC mode
- Provides 90 minutes of emergency operation
- Fully automatic solid-state two rate charger recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Standard self-diagnostic feature performs monthly, bi-annual, and annual tests to ensure reliable operation and meets electrical and life safety codes
- Field-selectable wiring allows for AC operation of unit to be controlled using a wall-switch, photocell or other switching mechanism
- Standard normally-on or normally-off and switched circuit
- Durable powder-coated finishes in white, black, nickel and dark bronze finish
- Available on QuickShip

SPECIFICATIONS

- HOUSING Powder coated finish on die-cast aluminum housing. Sealed and gasketed.
- ELECTRICAL Universal 120-277 voltage. 12.0 watts (2 LEDs x 6.0 watt) per unit. 4.8V long life, maintenance-free, rechargeable NiCd battery.
- MOUNTING Universal knockout pattern on back plate for wall mount. Threaded opening at the top of the enclosure for conduit mount.
- LISTINGS Listed to UL 924 standard as an emergency light suitable for wet locations (0°C - +50°C). Meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- WARRANTY 5-year limited warranty.

ORDERING EXAMPLE: EMER/DECO - DBR - OPTIONS - D

ORDERING INFO

SERIES HOUSING COLOR **OPTIONS** VOLTAGE EMER/DECO DBR Dark bronze [1] LT Low temperature [2] D 120 - 277V **BLK** Black WHT White NKL Nickel

QUICKSHIP


EMER/DECO-DBR-QS-D

NOTES

- Standard.
- For cold temperature applications -20°C 40°C



CROSS SECTIONS



FIXTURE DETAILS

BACKVIEW

BOLT CIRCLE PATTERN

Not to scale.



