



CATALOG #: _____

Type: _____

PROJECT: _____

FEATURES

- New York City compliant 8" tall red letters
- Compact, low profile design
- UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination
- Available as full-time AC powered unit or emergency unit with battery backup
- EM unit provides 90 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs
- Fully automatic solid-state two rate charger on EM unit recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Directional indicators can be installed on-site
- Self-diagnostic option performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes

ORDERING EXAMPLE: EXIT/EL/NYC - SF - CP - AN - AC - OPTIONS - D

ORDERING INFO

SERIES	NUMBER OF FACES	FACEPLATE FINISH	HOUSING COLOR	POWER OPTIONS
EXIT/EL/NYC	SF Single face	CP Clear Panel ^[2]	BLK Black	AC AC operation
	DF Double face ^[1]	MP Mirror Panel	AN Anodized aluminum	EM AC operation with emergency battery backup
		WP White Panel	WHT Industry-standard white	

OPTIONS	VOLTAGE
SDT Self-diagnostic test ^[3]	D 120V/277V
PC2 Polycarbonate shield ^[4]	SV__ Special voltage ^[5]

SPECIFICATIONS

- HOUSING – Premium-grade, extruded aluminum housing.
- ELECTRICAL – Dual 120/277 voltage standard. 4.8V long life, maintenance-free, rechargeable NiCd battery when specified with EM power option.
- MOUNTING – Aluminum mounting canopy for ceiling, side, or wall mount installation.
- LISTINGS –
 - UL 924 standard as an exit light suitable for dry or damp locations (0°C - +50°C).
 - Meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
 - Certified to CEC under Title 20 Regulations.
- WARRANTY – 5-year limited warranty.

NOTES

- ¹ MP and WP faceplate finish only.
- ² Single face only.
- ³ EM only.
- ⁴ Wall mount only. Ships separately. See page 2 for OPTIONS DETAILS.

⁵ Not available with SDT. UL Listed for 208/220/240 Volt, 50/60Hz.

EXIT/EL/NYC ^{LED} New York City-Approved Edge-Lit Exit Sign

FIXTURE DETAILS

Directional indicators provided for field installation.



OPTIONS DETAILS

Wall mount only. Ships separately.

PC2



DIMENSIONS: 15" x 22" x 7-3/4"