

CATALOG #: _____

Type: _____

PROJECT: _____



FEATURES

- Selectable red or green LEDs on-site with a built-in switch
- Compact, low-profile design
- Available as full-time AC powered unit or emergency unit with battery backup
- EM unit provides 90 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs
- Fully automatic solid-state two rate charger on EM units recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Unique design allows double face conversion in the field
- Removable directional indicators
- Dual circuit option enables connection to two different power supplies at the same time
- Available on QuickShip at hew.com/EXIT_quickship.pdf

ORDERING EXAMPLE: EXIT - RG - EM - WHT - OPTIONS - D

SERIES	LETTER COLOR	POWER OPTIONS	HOUSING COLOR
EXIT	RG Field-selectable red or green	AC AC operation EM AC operation with emergency battery backup	WHT Industry-standard white BLK Black

OPTIONS	VOLTAGE
SALIDA Salida faceplate ^[1]	D 120V/277V
DC Dual circuit ^[2]	120 120V
PC1 Polycarbonate shield ^[3]	277 277V
WG Wireguard, white ^[4]	

SPECIFICATIONS

- **HOUSING** – Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- **ELECTRICAL** – Dual 120/277 voltage standard. 1.2V long life, maintenance-free, rechargeable NiCd battery when specified with EM power option.
- **MOUNTING** – Mounting canopy for top or end mount. Universal knockout pattern on back plate for wall mount.
- **LISTINGS** –
 - UL924 standard as an exit light suitable for dry or damp locations (0°C to 50°C).
 - Meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
 - Certified to CEC under Title 20 Regulations.
- **WARRANTY** – 5-year limited warranty.

NOTES

- ¹ Industry-standard white only.
² AC Power Option only. Must specify 120V or 277V.
³ Wall mount only. Ships separately. See page 2 for OPTIONS DETAILS.
⁴ Wall mount only. Ships separately. See page 2 for OPTIONS DETAILS.

ELECTRICAL INFORMATION

	INPUT WATTS (W)	INPUT AMPS (A)
120V	1.0	0.1
277V	1.0	0.1

FIXTURE DETAILS

RED



GREEN




DIRECTIONAL INDICATOR KNOCKOUTS



OPTIONS DETAILS


Wall mount only. Ships separately.

PC1



DIMENSIONS: 13-3/16" x 9-3/16" x 2-1/2"

WG



DIMENSIONS: 13-3/4" x 15-1/4" x 6"