M6PR LED
6″ MRI Shallow Plenum Downlight – Round



L10 – L30 Lumens shown

CATALOG #:

TYPE:

PROJECT:

BAA & BABA COMPLIANT | CCEA Approved | IP65 Rated | Low UGR | WET/CC | TW | TrimLock®

ORDERING EXAMPLE: M6PR - TL - L20/835 - OPTIONS - LW - OF - WH - TRIM OPTIONS - N - F1M
(HOUSING | TRIM | MOUNT.)

HOUSING

SERIES	LUMENS [1]	CRI	CCT	OPTIONS
M6PR - TL TrimLock	**L10** 1,000lm	**8** 80	**27** 2700K	**ATH** Airtight construction
	L15 1,500lm	**9** 90 [3]	**30** 3000K	**CP** Chicago plenum (CCEA) [4]
	L20 2,000lm		**35** 3500K	
	L30 3,000lm		**40** 4000K	
	L40 4,000lm		**50** 5000K	
	L50 5,000lm [2]		**TW** Tunable White (80 CRI, 2700K-5000K)	

TRIM [5]

TRIM TYPE	DISTRIBUTION [6]	FLANGE TYPE	REFLECTOR FINISH	TRIM OPTIONS
L Flush lens	**W** 85° Wide	**OF** 1/2″ standard flange	**CS** Clear semi-specular powder coat	**IP** IP65 rated trim
	M 35° Medium		**WH** White texture powder coat	**AD** Diffuse acrylic lens [7]
	N 25° Narrow		**BL** Black texture powder coat	**PD** Diffuse 1/8″ polycarbonate lens [8]
				WET/CC Wet location, covered ceiling listed
				AM Anti-microbial [9]

MOUNTING

MOUNTING TYPE [10]	MOUNTING HARDWARE [11]
N Open pan for new construction	**F1M** Factory-installed 2-position fixed pan bracket, universal bar hanger included [13]
I IC-rated enclosure for new construction [12]	**BA1M** Adjustable butterfly pan bracket, aluminum, bar hanger not included [14]
	CA1M Adjustable caterpillar pan bracket, aluminum, universal bar hanger included [15]

REMOTE DRIVER ENCLOSURE (ORDERED SEPARATELY) [16]

ORDERING EXAMPLE: M6PR - RDB1 - L10 - OPTIONS - DIM - UNV

SERIES	DRIVER BOX	DRIVER QTY.	LUMENS	OPTIONS	DRIVER [17]	VOLTAGE
M6PR	**RDB** Remote driver enclosure	**1** **7**	**L10** 1,000lm	**EM/10W** 10-watt emergency battery [19]	*See page 4 for ADDITIONAL DRIVER OPTIONS.*	**UNV** 120-277V
		2 **8**	**L15** 1,500lm	**EM/7W** 7-watt emergency [20]	**DIM** Dimming driver, 0-10V [22]	**347** 347V [24]
		3 **9**	**L20** 2,000lm	**F** Fuse kit	**DIM1** 1% Dimming driver, 0-10V [23]	
		4 **10**	**L30** 3,000lm	**SDT** Stepdown transformer [21]	**DMX** Driver prewired for DMX applications	
		5 **11**	**L40** 4,000lm			
		6 **12**	**L50** 5,000lm [18]			

NOTES

1. Lumen output based on W Distribution and WH Reflector Finish, 80 CRI, 3500K for static white and 4000K for tunable white. Actual performance may vary +/-5%. See page 2 for FIXTURE PERFORMANCE DATA.
2. Available with RDB1 only. Not available with tunable white.
3. Not available with tunable white.
4. I Mounting Type required.
5. Trim ships separately.
6. Beam angle based on WH Reflector Finish.
7. W Distribution only.
8. W Distribution only.
9. WH and BL Reflector Finishes only.
10. Mounting hardware required, ordered separately, see MOUNTING HARDWARE ordering info. See page 3 for MOUNTING TYPE DETAILS.
11. See page 3 for MOUNTING HARDWARE DETAILS.
12. L30 lumen package max.
13. Universal bar hanger ships uninstalled.
14. N Mounting Type only.
15. N Mounting Type only.
16. Required. Ordered as a separate catalog number, ships separately. See page 4 for REMOTE DRIVER ENCLOSURE DETAILS (ORDERED & SHIPPED SEPARATELY).
17. All drivers dimmed by single control signal.
18. Available with RDB1 only. Not available with tunable white.
19. Available with RDB1 only. Not available with L10 lumen package. Specify CEC in the option code when California Energy Commission regulations are required.
20. Specify CEC in the option code when California Energy Commission regulations are required.
21. May be required for 347V, see product builder at hew.com/product-builder
22. 0.1% Driver with tunable white.
23. Not available with tunable white.
24. Not available with Tunable White, EM batteries or DMX Driver.

M6PR LED
6" MRI Shallow Plenum Downlight – Round

FEATURES

- Innovative TrimLock reflector retention system ensures trim remains flush with ceiling plane
- Designed with non-ferrous materials for MRI imaging suites
- IP65-rated die-cast trim includes easy-to-clean flush lens
- Slim 5" depth for minimal plenum space applications
- Beam angles ranging from 25° narrow to 85° wide for tailored performance
- Support human-centric design with adaptive, individualized lighting using tunable white light
- Fully room-side accessible
- Low UGR meets LEED and WELL requirements
- Made Right Here® in the USA

SPECIFICATIONS

- HOUSING – Spun housing with forged aluminum heat sink. Aluminum splice compartment. Trim housing adjusts for ceiling thickness from 1/2" - 1-1/2".
- TRIMLOCK – Innovative TrimLock reflector retention system ensures the trim remains flush with the ceiling plane.
- LENSED TRIM – Die-cast aluminum frame with micro-prismatic, acrylic lens.
- ELECTRICAL – High-performance Class 2 C.O.B. LED array. Modular quick-connect plug for easy field-connection of LED light assembly to splice compartment. Reported L70>55,000 hours. Reported L90>55,000 hours. Estimated L70 = 200,000 hours. Remote mounted driver enclosure required, ordered separately, must be located outside MRI room, RF filter required, provided by others. Tunable White products use LEDs of multiple CCTs and may produce a perceptibly different shade of white from single-CCT products at the same CCT. All CCTs are within 3 MacAdam ellipses.
- MOUNTING – Recessed. Aluminum mounting pan for new construction or IC-rated enclosure. Minimum 24" O.C. marked spacing required for L50 lumen package. Remote mounted driver box must be located outside MRI room, RF filter required, provided by others.
- LISTINGS –
  - cCSAus conforms to UL STD 1598; Certified to CAN/CSA STD C22.2 No. 250.0 for damp locations. LED light assembly conforms to UL 2108 for remote installation.
  - Suitable for wet location under covered ceiling when specified with WET/CC option.
  - IC-rated for direct contact with insulation when specified with I Mounting Type.
  - City of Chicago Environmental Air approved when specified with CP option.
  - IP65 rated trim when specified with IP option.
  - Complies with ASTM-E283 when specified with ATH option.
  - RoHS compliant.
  - Build America, Buy America (BABA) and Buy American Act (BAA) compliant. Request certification at hew.com/buy-american
- WARRANTY – 5-year limited warranty, see hew.com/warranty

FIXTURE PERFORMANCE DATA

	DISTRIBUTION	DELIVERED LUMENS	WATTAGE	EFFICACY (lm/W)
L10	W	1111	10.7	104
	M	1127	10.7	105
	N	1137	10.7	106
L15	W	1696	16.6	102
	M	1720	16.6	104
	N	1736	16.6	105
L20	W	2208	22.7	97
	M	2239	22.7	99
	N	2260	22.7	100
L30	W	3293	33.2	99
	M	3309	33.2	100
	N	3224	33.2	97
L40	W	4394	44.1	100
	M	4415	44.1	100
	N	4302	44.1	98
L50	W	5503	54.7	101
	M	5529	54.7	101
	N	5388	54.7	99

- Photometrics tested in accordance with IESNA LM-79. Results based on O Trim Type, W Distribution, CS Reflector Finish, 80 CRI, 3500K for single CCT and 4000K for tunable white, wattage for 120V input, and 25°C ambient temperature. Actual performance may vary +/-5%
- To calculate lumen output in emergency mode, multiply the battery wattage by the efficacy.
- Use multiplier tables to calculate additional options.

MULTIPLIER TABLES

	COLOR TEMPERATURE		
	CCT	SINGLE CCT	TW
80 CRI	2700K	0.92	0.83
	3000K	0.98	1.00
	3500K	1.00	0.99
	4000K	1.01	1.00
	5000K	1.02	0.98
90 CRI	2700K	0.76	–
	3000K	0.79	–
	3500K	0.82	–
	4000K	0.84	–
	5000K	0.88	–

TRIM	
CATALOG NUMBER	CONVERSION FACTOR
AD	0.85
PD	0.85

TUNABLE WHITE



PHOTOMETRY

M6PR-TL-L20/835-LW-OF-WH Total Luminaire Output: 2208 lumens; 22.7 Watts | Efficacy: 97.3 lm/W | 80 CRI; 3500K CCT



CANDLEPOWER DISTRIBUTION	VERTICAL ANGLE	HORIZONTAL ANGLE 0°	ZONAL LUMENS
	0	1169	
	5	1148	81
	15	1075	174
	25	989	243
	35	859	267
	45	556	183
	55	223	86
	65	111	47
	75	51	21
	85	12	3
	90	1	

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 40	1399	64
	0 - 60	2029	92
	0 - 90	2208	100
	0 - 180	2208	100


85° Wide


35° Medium


25° Narrow

M6PR LED
6″ MRI Shallow Plenum Downlight – Round

TRIMLOCK INSTALLATION DETAILS

TWIST

PULL

RELEASE

REFLECTOR FINISH DETAILS

CS
Clear semi-specular

WH
White

BL
Black



CROSS SECTIONS

Ceiling cutout ø6-1/2″

L10 – L30 LUMENS



L40 – L50 LUMENS



MOUNTING TYPE DETAILS

NEW CONSTRUCTION



IC-RATED



	LENGTH			
LUMENS	A	B	C	D
L10 - L30	15-3/16″	16″	4-1/8″	12-1/8″

MOUNTING HARDWARE DETAILS

F1M Factory-installed 2-position fixed pan bracket, universal bar hanger included



BA1M Adjustable butterfly pan bracket, aluminum, bar hanger not included (N Mounting Type only)



CA1M Adjustable caterpillar pan bracket, aluminum, universal bar hanger included (N Mounting Type only)



M6PR LED
6″ MRI Shallow Plenum Downlight – Round

REMOTE DRIVER ENCLOSURE DETAILS (ORDERED & SHIPPED SEPARATELY)

SINGLE FIXTURE



SINGLE FIXTURE WITH EM BATTERY



2 - 8 FIXTURES



9 - 12 FIXTURES



ADDITIONAL DRIVER OPTIONS

Restrictions may apply and 347V may require stepdown transformer, consult product builder at hew.com/product-builder. I Mounting Type not available with Lutron controls.

CATALOG NUMBER	DESCRIPTION
DIM	Driver with external dimming wires prewired for 0-10V low voltage applications (tunable white: (1) 0-10V signal controls 0.1% dimming and (1) 0-10V signal controls CCT)
DIM1 [1]	1% driver with external dimming wires prewired for 0-10V low voltage applications
DALI	DALI dimming driver
DMX	Driver prewired for DMX applications
LDE1 [1]	Lutron Hi-lume 1% EcoSystem dimming driver
LD2	Lutron DALI-2 digital driver, 1%

1 Single CCT only.