


W4CR^{LED} 4" Wet Location Compact Cylinder – Round



CATALOG #: _____

TYPE: _____

PROJECT: _____



TwistLock™

FEATURES

- Sleek architectural form delivers refined, high-performance outdoor illumination
- Slim profile enables precise light control, highlighting facades and design details
- Compact build saves space in tight installations and low-clearance areas
- Versatile pendant, wall, and canopy-mount maximize application flexibility
- Durable aluminum housing and die-cast trim engineered for year-round exposure
- Sealed IP66-rated design guards internal components from water, dust, and debris
- Simple lift-and-twist surface and pendant mount secures trim skirt to junction box
- Beam angles ranging from 21° spot to 56° wide for tailored performance
- Pairs with Williams indoor cylinders for seamless exterior-to-interior continuity
- Maximize energy savings with efficacies up to 126 lm/W
- Made Right Here® in the USA

SPECIFICATIONS

- **HOUSING** – Extruded aluminum with die-cast aluminum accent ring.
- **FINISH** – Super durable polyester powder coat bonded to phosphate-free, multi-stage pretreated metal, meets and exceeds AAMA 2604 specifications for outdoor durability. Salt spray tested, 3,000 hours (ASTM B117).
- **TRIM** – Die-cast aluminum frame with micro-prismatic, glass lens.
- **ELECTRICAL** – High-performance Class 2 C.O.B. LED array. Modular quick-connect plug for easy field-connection of LED light assembly to driver. Estimated L70>105,000 hours. 50/60 Hz, THD <10%. Rated -10°C to 40°C ambient operating temperature (-30°C with LA option; 0°C to 40°C with standard EM battery).
- **MOUNTING** – Surface, pendant, or wall mount.
- **LISTINGS** –
 - cCSAus conforms to UL STD 1598 and UL STD 8750. Certified to CAN/CSA STD C22.2 No. 250.2-20. Suitable for wet locations.
 - ANSI/UL Standard 2108
 - IP66 rated
 - Build America, Buy America (BABA) and Buy American Act (BAA) compliant. Request certification at hew.com/buy-american
- **WARRANTY** – 5-year limited warranty, see hew.com/warranty

ORDERING EXAMPLE: W4CR - 08 - L20/835 - OPTIONS - WHT - DIM - UNV - W - WM

SERIES	HEIGHT	LUMENS ^[1]	CRI	CCT	OPTIONS ^[2]
W4CR	08 8"	L10 1,000lm	8 80	27 2700K	EM/10WRM/IPRTS Remote mount 10-watt emergency battery with IP65 rated regressed test switch ^[3] -30°C low ambient operating temperature ^[4] Remote mount control/driver box, galvanized steel ^[5] Additional lower lumen packages available ^[6] Example: 1,800 lumens = W4CR-08-L20/835-(L18)
		L15 1,500lm	9 90	30 3000K	
		L20 2,000lm		35 3500K	
		L25 2,500lm		40 4000K 50 5000K	
					LA RDB (L__)

HOUSING FINISH^[7]

BLK Black (RAL #9004)
DBZ Dark bronze
DBR Medium bronze
GRAY Standard gray
GRN Green (RAL #6005)
SLV Satin aluminum (RAL #9006)
WHT White (RAL #9003)

DRIVER

See page 2 for **ADDITIONAL DRIVER OPTIONS**.
DIM Dimming driver, 0-10V
DIM1 1% Dimming driver, 0-10V

VOLTAGE

UNV 120-277V
347 347V^[8]

DISTRIBUTION

W 56° Wide
M 40° Medium
N 30° Narrow
S 21° Spot

MOUNTING^[9]

RDB Option required with surface and pendant mount.

Recessed J-Box

WM Wall mount to recessed J-box^[10]
SM Surface mount to recessed J-box^[11]
PM__ Pendant mount to recessed J-box^[12]
Specify length in 1" increments, minimum 6".
Example: 24" pendant = **PM24**

Surface J-Box with Conduit Entry Cover

WMS Wall mount to surface J-box^[13]
SMS Surface mount to surface J-box^[14]
PMS__ Pendant mount to surface J-box^[15]
Specify length in 1" increments, minimum 6".
Example: 24" pendant = **PMS24**

NOTES

- ¹ Lumen output based on W Distribution and 80 CRI/3500K CCT. Actual performance may vary +/-5%. See page 2 for FIXTURE PERFORMANCE DATA.
- ² See page 2 for EMERGENCY BATTERY DETAILS. All EM batteries are California Energy Commission (CEC) Compliant.
- ³ Max remote distance 50', including suspension length. Large remote box provided.
- ⁴ RDB Option required. Only available with DIM Driver. Not available with EM/10WRM/IPRTS Option.
- ⁵ Required when specified with pendant or surface mounting.
- ⁶ Specify in increments of 100 nominal lumens. Option must be specified with next higher lumen package.

- ⁷ See page 3 for HOUSING FINISH DETAILS.
- ⁸ Not available with EM batteries or DMX drivers.
- ⁹ See page 3 for MOUNTING DETAILS. RDB Option required with surface and pendant mount.
- ¹⁰ 4" square galvanized J-box, by others. Driver restrictions may apply. See page 2 for ADDITIONAL DRIVER OPTIONS.
- ¹¹ 4" octagonal galvanized J-box, by others.
- ¹² Canopy and pendant match fixture housing color unless specified otherwise. 4" octagonal galvanized J-box, by others.
- ¹³ 4" round cast aluminum weatherproof J-box, by others.
- ¹⁴ 4" round cast aluminum weatherproof J-box, by others.
- ¹⁵ Canopy and pendant match fixture housing color unless specified otherwise. 4" round cast aluminum weatherproof J-box, by others.



W4CR LED

4" Wet Location Compact Cylinder – Round

FIXTURE PERFORMANCE DATA

	DISTRIBUTION	DELIVERED LUMENS	WATTAGE	EFFICACY (lm/W)
L10	W	1061	9.8	108
	M	1043	9.8	106
	N	1106	9.8	113
	S	1161	9.8	118
L15	W	1564	13.6	115
	M	1538	13.6	113
	N	1630	13.6	120
	S	1712	13.6	126
L20	W	2087	18.1	115
	M	2051	18.1	113
	N	2173	18.1	120
	S	2283	18.1	126
L25	W	2590	23.1	112
	M	2546	23.1	110
	N	2698	23.1	117
	S	2833	23.1	123


MULTIPLIER TABLE

COLOR TEMPERATURE	
CCT	CONVERSION FACTOR
2700K	0.98
3000K	1.00
3500K	1.00
4000K	1.01
5000K	0.99

80 CRI	2700K	0.94
	3000K	0.96
	3500K	0.97
	4000K	0.97
	5000K	0.95

- Photometrics tested in accordance with IESNA LM-79. Results based on W Distribution and 80 CRI/3500K CCT, average wattage for 120V input, and 25°C ambient temperature. Actual performance may vary +/-5%.
- To calculate lumen output in emergency mode, multiply the battery wattage by the efficacy.
- Use multiplier table to calculate additional options.

DISTRIBUTION CURVES



ADDITIONAL DRIVER OPTIONS


Driver located in arm when specified with wall mount.

DRIVER	DESCRIPTION	RDB DETAILS BY LUMEN STOP				
		L10	L15	L20	L25	10W EM
DIM	Dimming driver prewired for 0-10V low voltage applications	R S	R S	R S	R S	R L
DIM1	1% dimming driver prewired for 0-10V low voltage applications	R S	R S	R S	R S	R L
DIM LINE	Line voltage dimming driver (TRIAC and ELV compatible at 120V only)	–	R S	R S	R S	R L
DMX	0.1% dimming driver for DMX controls	R M	R M	R M	R M	R L
DALI	DALI dimming driver	R M	R M	R M	R M	R L
LDE1	Lutron Hi-lume 1% EcoSystem dimming LED driver	R M	R M	R M	R M	R L


REMOTE MOUNT KEY	
R S	RDB Required, Small Box
R S	RDB Required, Small Box (optional with wall mount)
R M	RDB Required, Medium Box
R L	RDB Required, Large Box

REMOTE MOUNT DETAILS

Max remote distance is 50' including suspension length, connection by others. Must be room-side accessible and mounted in dry/damp location.








EMERGENCY BATTERY DETAILS



W4CR^{LED} 4" Wet Location Compact Cylinder – Round

HOUSING FINISH DETAILS

WHITE	BLACK	GREEN	MEDIUM BRONZE	DARK BRONZE	SATIN ALUMINUM	GRAY	RAL# _____	For custom color, please specify RAL code or a manufacturer code with description. All custom colors other than RAL require four sample swatches, minimum 1" square.
								

MOUNTING DETAILS


WALL MOUNT

WM



Secures to 4" square galvanized recessed J-box, by others

Side View




WMS




Secures to 4" round cast aluminum weatherproof J-box, by others


Side View



TOP VIEW



ADAPTOR




SURFACE MOUNT

SM




Secures to 4" octagonal galvanized recessed j-box, by others



SMS



Secures to 4" round cast aluminum weatherproof J-box, by others




PENDANT MOUNT

Provided with 1/2" IPS Threaded stem. Specify length of stem, 6" minimum, 24" default length.

PM__



Secures to 4" octagonal galvanized recessed j-box, by others



PMS__



Secures to 4" round cast aluminum weatherproof J-box, by others

